

Statement of Basis of the Federal Operating Permit

Celanese Ltd.

Site Name: Clear Lake Plant
Area Name: Ethylene Oxide/Ethylene Glycol
Physical Location: PO Box 58190
Nearest City: Houston
County: Harris

Permit Number: O1986
Project Type: Renewal

Standard Industrial Classification (SIC) Code: 2869
SIC Name: Industrial Organic Chemicals

This Statement of Basis sets forth the legal and factual basis for the draft permit conditions in accordance with 30 TAC §122.201(a)(4). Per 30 TAC §§ 122.241 and 243, the permit holder has submitted an application under § 122.134 for permit renewal. This document may include the following information:

- A description of the facility/area process description;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: April 21, 2017

Operating Permit Basis of Determination

Permit Area Process Description

Ethylene Oxide (EO) Unit

EO is made by catalytic direct oxidation of ethylene with pure oxygen. The reaction is exothermic, and heat is removed from the reactors using high-grade kerosene. Reactor effluent gases are cooled and sent to EO absorber columns where EO is recovered in water. Remaining gases are recycled back to the reactors. CO₂ is the main byproduct of the reaction, and a portion of the recycle gas stream is circulated through a CO₂ removal system. CO₂ removed from the stream goes to an incinerator, and remaining gas goes back to recycle. Water containing the absorbed EO goes to a stripper, and the EO overhead is purified by distillation. Water is recovered and recycled as lean absorbent to the EO absorber. Purified EO is the finished product.

Ethylene Glycol (EG) Unit

EG is made by the non-catalytic liquid phase hydrolysis of EO with water in reactors. EG is concentrated in three stages, and excess water is removed and recycled back to the reactors. The concentrated EG goes to purification columns, where EG is separated and sent to product storage. Heavier glycols are further purified and sent to product storage.

FOPs at Site

The “application area” consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O1893, O3678

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO ₂ , PM, NO _x , HAPS, CO
------------------	---

Reading State of Texas’s Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as “applicable requirements”) that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting
 - Additional Monitoring Requirements
 - New Source Review Authorization Requirements

- Compliance Requirements
- Protection of Stratosphere Ozone
- Permit Location
- Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often

required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed after January 31, 1972 which are limited, over a six-minute average, to 20% opacity as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	No
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	Yes
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	Yes
CSAPR (Cross-State Air Pollution Rule)	No

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.
8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability

determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column "Changes and Exceptions to RRT." If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word "None" will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled "Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected."

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled "Basis for Applying Permit Shields" specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*
32MN1138	30 TAC Chapter 117, Subchapter B	R7ICI-1	<p>Fuel Flow Monitoring = Unit is a diesel engine operating with a run time meter and using monthly fuel use records maintained for each engine per 30 TAC §§ 117.140(a)(2)(C), 117.340(a)(2)(C) or 117.440(a)(2)(C).</p> <p>NOx Emission Limitation = Title 30 TAC §§ 117.310(d)(3) and 117.310(a)(9)</p> <p>CO Emission Limitation = Title 30 TAC § 117.310(c)(1) 3 g/hp-hr option</p> <p>CO Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>CO Monitoring System = Emissions monitored by means other than a CEMS or PEMS.</p> <p>EGF System Cap Unit = Engine is not used as an electric generating facility to generate electricity for sale to the electric grid.</p> <p>Type of Service = Used exclusively in emergency situations [claiming the emergency service exemption under 30 TAC §§ 117.103(a)(6)(D), 117.203(a)(6)(D), 117.303(a)(6)(D) or 117.403(a)(7)(D)]</p> <p>Fuel Fired = Petroleum-based diesel fuel</p> <p>NOx Averaging Method = Complying with the applicable emission limit using a block one-hour average.</p> <p>NOx Reduction = None</p> <p>ESAD Date Placed in Service = Placed into service before October 1, 2001 and has not been modified, reconstructed or relocated on or after October 1, 2001.</p> <p>NOx Monitoring System = Maximum emission rate testing in accordance with 30 TAC § 117.8000</p> <p>Diesel HP Rating = Horsepower rating is 300 hp or greater, but less than 600 hp.</p>
32MN1138	40 CFR Part 63, Subpart ZZZZ	63ZZZZ	<p>HAP Source = Any stationary source or group of stationary sources of hazardous air pollutants meeting the definition of a major source as described in 40 CFR § 63.2.</p> <p>Brake HP = Stationary RICE with a brake HP greater than or equal to 300 HP and less than or equal to 500 HP.</p> <p>Construction/Reconstruction Date = Commenced construction or reconstruction before December 19, 2002.</p> <p>Displacement = The stationary CI RICE has a displacement less than 30 liters per cylinder and uses diesel fuel.</p> <p>Service Type = Emergency use where the RICE operates or is contractually obligated to be available for more than 15 hours per calendar year as specified in 40 CFR §63.6640(f)(2)(ii)-(iii) or that operates for the purpose specified in 40 CFR §63.6640(f)(4)(ii).</p> <p>Stationary RICE Type = Compression ignition engine</p>
32SU0006	30 TAC Chapter 115, Storage of VOCs	R5115-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
32SU0016A	30 TAC Chapter 115, Storage of VOCs	R5115-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
32SUAREA	30 TAC Chapter 115, Storage of VOCs	R5115-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
32V1182	30 TAC Chapter 115, Storage of VOCs	30TAC-01	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
32V1182	40 CFR Part 60, Subpart Kb	60Kb-01	Product Stored = Petroleum liquid (other than petroleum or condensate) Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
32V145	30 TAC Chapter 115, Storage of VOCs	30TAC-01	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
32V145	40 CFR Part 60, Subpart Kb	60Kb-01	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
32V193	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor recovery unit
32V193	30 TAC Chapter 115, Storage of	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		<p>with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor recovery unit</p>
32V193	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a process</p>
32V194	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor recovery unit</p>
32V194	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor recovery unit</p>
32V194	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			kPa) Emission Control Type = Emissions routed to a process
32V195	30 TAC Chapter 115, Storage of VOCs	R5112-1	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor recovery unit
32V195	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor recovery unit
32V195	40 CFR Part 63, Subpart G	63G119-1	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is subject to § 63.172 of Subpart H NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a process
32V220	30 TAC Chapter 115, Storage of VOCs	30TAC-01	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
32V220	40 CFR Part 60, Subpart Kb	60Kb-01	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
32V222	30 TAC Chapter 115, Storage of	30TAC-01	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance

Unit ID	Regulation	Index Number	Basis of Determination*
	VOCs		<p>with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
32V222	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia</p>
32V306	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor recovery unit</p>
32V306	30 TAC Chapter 115, Storage of VOCs	R5112-2	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p> <p>Control Device Type = Other vapor recovery unit</p>
32V306	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G).</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p> <p>Bypass Lines = Closed vent system has no by-pass lines.</p> <p>Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa)</p> <p>Emission Control Type = Emissions routed to a process</p>
32V34	30 TAC Chapter 115, Storage of VOCs	R5112-1	<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank using a vapor recovery system (VRS)</p> <p>True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor recovery unit
32V34	30 TAC Chapter 115, Storage of VOCs	R5112-2	Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank using a vapor recovery system (VRS) True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons Control Device Type = Other vapor recovery unit
32V34	40 CFR Part 63, Subpart G	63G119-1	MACT Subpart F/G Applicability = The unit is a Group 1 vessel (as defined in Table 5 for existing sources or Table 6 for new sources of 40 CFR 63, Subpart G). Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system, or is subject to § 63.148 of Subpart G NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. Hard Piping = The closed vent system is constructed of hard piping. Bypass Lines = Closed vent system has no by-pass lines. Maximum TVP = Maximum true vapor pressure of the total organic HAP in the liquid is greater than or equal to 11.11 psi (76.6 kPa) Emission Control Type = Emissions routed to a process
33V149	30 TAC Chapter 115, Storage of VOCs	R5115-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
33V168	30 TAC Chapter 115, Storage of VOCs	R5115-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
33V168	40 CFR Part 63, Subpart G	63G119-1	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
33V169	30 TAC Chapter	R5115-1	Today's Date = Today's date is March 1, 2013 or later.

Unit ID	Regulation	Index Number	Basis of Determination*
	115, Storage of VOCs		<p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V169	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
33V170	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V170	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>
33V171	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
33V171	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>
33V172	30 TAC Chapter 115, Storage of VOCs	R5115-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V172	40 CFR Part 60,	60Kb-01	<p>Product Stored = Volatile organic liquid</p>

Unit ID	Regulation	Index Number	Basis of Determination*
	Subpart Kb		Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)
33V173	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
33V173	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>
33V174	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
33V174	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>
33V191	30 TAC Chapter 115, Storage of VOCs	R5115-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V191	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
33V192	30 TAC Chapter 115, Storage of VOCs	R5115-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>

Unit ID	Regulation	Index Number	Basis of Determination*
33V192	40 CFR Part 63, Subpart G	63G119-1	MACT Subpart F/G Applicability = The unit is a Group 2 vessel. NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y. NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
33V198	30 TAC Chapter 115, Storage of VOCs	30TAC-01	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
33V198	40 CFR Part 60, Subpart Kb	60Kb-01	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
33V200	30 TAC Chapter 115, Storage of VOCs	30TAC-01	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 40,000 gallons
33V200	40 CFR Part 60, Subpart Kb	60Kb-01	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia
33V201	30 TAC Chapter 115, Storage of VOCs	30TAC-01	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria. Tank Description = Tank does not require emission controls True Vapor Pressure = True vapor pressure is less than 1.0 psia Product Stored = VOC other than crude oil or condensate Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons
33V201	40 CFR Part 60, Subpart Kb	60Kb-01	Product Stored = Volatile organic liquid Storage Capacity = Capacity is greater than or equal to 19,800 gallons (75,000 liters) but less than 39,900 gallons (151,000 liters) Maximum True Vapor Pressure = True vapor pressure is less than 2.2 psia
33V225	30 TAC Chapter 115, Storage of VOCs	R5115-1	Today's Date = Today's date is March 1, 2013 or later. Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V225	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
33V23	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V23	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>
33V24	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V24	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is greater than or equal to 39,900 gallons (151,000 liters)</p> <p>Maximum True Vapor Pressure = True vapor pressure is less than 0.5 psia</p>
33V343	30 TAC Chapter 115, Storage of VOCs	R5115-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V343	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.
33V365	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
33V365	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>
33V366	30 TAC Chapter 115, Storage of VOCs	R5115-1	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 40,000 gallons</p>
33V366	40 CFR Part 63, Subpart G	63G119-1	<p>MACT Subpart F/G Applicability = The unit is a Group 2 vessel.</p> <p>NESHAP Subpart Y Applicability = The unit is not subject to 40 CFR Part 61, Subpart Y.</p> <p>NSPS Subpart Kb Applicability = The unit is not subject to 40 CFR Part 60, Subpart Kb.</p>
36V1171	30 TAC Chapter 115, Storage of VOCs	30TAC-01	<p>Today's Date = Today's date is March 1, 2013 or later.</p> <p>Alternate Control Requirement = Not using an alternate method for demonstrating and documenting continuous compliance with applicable control requirements or exemption criteria.</p> <p>Tank Description = Tank does not require emission controls</p> <p>True Vapor Pressure = True vapor pressure is less than 1.0 psia</p> <p>Product Stored = VOC other than crude oil or condensate</p> <p>Storage Capacity = Capacity is greater than 1,000 gallons but less than or equal to 25,000 gallons</p>
36V1171	40 CFR Part 60, Subpart Kb	60Kb-01	<p>Product Stored = Volatile organic liquid</p> <p>Storage Capacity = Capacity is less than 10,600 gallons (40,000 liters)</p>
32EOLD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Control Device Type = Control device other than a flare, vapor combustor, catalytic incinerator, direct flame incinerator, chiller, or carbon adsorption system.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor control system that maintains a control efficiency of at least 90%.</p>
32EOLD	40 CFR Part 63, Subpart G	63G126-1	<p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are routed to a fuel gas system or to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is operated and maintained under negative pressure.</p>
33EGLD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>
33EGLD	40 CFR Part 63, Subpart G	63G126-1	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>
33UNITLD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-1	<p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure less than 0.5 psia.</p>
33UNITLD	30 TAC Chapter 115, Loading and Unloading of VOC	R5211-2	<p>Chapter 115 Control Device Type = No control device.</p> <p>Chapter 115 Facility Type = Facility type other than a gasoline terminal, gasoline bulk plant, motor vehicle fuel dispensing facility or marine terminal.</p> <p>Alternate Control Requirement (ACR) = No alternate control requirements are being utilized.</p> <p>Vapor Tight = Not all liquid and vapor lines are equipped with fittings which make vapor-tight connections that close automatically when disconnected.</p> <p>Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline.</p> <p>Transfer Type = Loading and unloading.</p> <p>True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.</p> <p>Daily Throughput = Daily throughput not determined since 30 TAC § 115.217(a)(2)(A) or 30 TAC § 115.217(b)(3)(A) exemption is not utilized.</p> <p>Control Options = Vapor balance system.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
33UNITLD	40 CFR Part 63, Subpart G	63G126-1	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
32FLR0001	30 TAC Chapter 111, Visible Emissions	R1111-1	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.
32FLR0001	30 TAC Chapter 111, Visible Emissions	R1111-2	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used only under emergency or upset conditions.
32FLR0001	30 TAC Chapter 115, HRVOC Vent Gas	R5722-1	Monitoring Requirements = Flare is complying with the continuous monitoring requirements of § 115.725(d). Out of Service = Flare was not permanently out of service by April 1, 2006. Total Gas Stream = Flare receives a total gas stream with greater than 100 ppmv HRVOC at some time. Gas Stream Concentration = Flare receives a gas stream containing 5% or greater HRVOC by weight at some time. Multi-Purpose Usage = Flare is used for abatement of emissions from scheduled or unscheduled maintenance, startup or shutdown activities AND as an emergency flare. Flow Rate = Flow rate of the gas routed to the flare is determined using process knowledge and engineering calculations. Alternative Monitoring = No alternative monitoring and test methods are used. Physical Seal = Flare is equipped with a flow monitor or indicator. Monitoring Operations = Using the flow monitoring requirements in § 115.725(d)(1) §115.725(h)(4) Alternative = Using the continuous monitoring requirements in § 115.725(d)(2). Minor Modificaiton = No minor modifications to the monitoring and test methods are used. Tank Service = Flare is not in dedicated service for storage tanks with 95% or greater of an individual HRVOC. Flare Type = Flare is in multi-purpose service.
EOEGFUG	30 TAC Chapter 115, HRVOC Fugitive Emissions	R5780-1	Agitators = The fugitive unit does not contain agitators. Alternative Work Practice in § 115.358 = No components are complying with the alternative work practice requirements in 30 TAC § 115.358. Compressor Seals = The fugitive unit contains compressor seals. Open-ended Valves or Lines = The fugitive unit contains open-ended valves or lines. Process Drains = The fugitive unit contains process drains. Title 30 TAC §115.780 Applicable = The fugitive unit contains a defined process and Highly Reactive VOC. Valves (not pressure relief, open-ended or bypass line valves) = The fugitive unit contains valves other than pressure relief, open-ended or bypass line valves. ACR = No open-ended valves or lines are complying with an alternate control requirement. Less Than 250 Components at Site = The fugitive unit is located at a site with at least 250 fugitive components in VOC service. Weight Percent HRVOC = Components in the fugitive unit contact process fluids that contain less than 5.0% HRVOC by weight and process fluids that contain HRVOC at 5.0%, or greater, by weight on an annual average basis. Complying with § 115.781(b)(9) = Process drains are complying with the requirements of § 115.781(b)(9). Pumps with Shaft Seal System = No pumps are equipped with a shaft sealing system that prevents or detects emission of VOC from the seal.

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Bypass Line Valves = The fugitive unit contains bypass line valves.</p> <p>Compressors with Shaft Seal System = No compressors are equipped with a shaft sealing system that prevents or detects emission of VOC from the seal.</p> <p>Flanges or Other Connectors = The fugitive unit contains flanges or other connectors.</p> <p>Heat Exchanger Heads, etc. = The fugitive unit contains heat exchanger heads, sight glasses, meters, gauges, sampling connections, bolter manways, hatches, sump covers, junction vent boxes or covers and seals on VOC water separators.</p> <p>Pressure Relief Valves = The fugitive unit contains pressure relief valves.</p> <p>Pump Seals = The fugitive unit does not contain pump seals.</p> <p>ACR = No pressure relief valves are complying with an alternate control requirement.</p> <p>Agitators with Shaft Seal System = No agitators are equipped with a shaft sealing system that prevents or detects emission of VOC from the seal.</p> <p>Complying with § 115.781(b)(9) = Pressure relief valves are complying with the requirements of § 115.781(b)(9).</p>
EOEGFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-1	<p>Agitators = The fugitive unit does not contain agitators.</p> <p>Components Utilizing Alternative Work Practice in § 115.358 = No components in the fugitive unit are using the alternative work practice under § 115.358.</p> <p>Compressor Seals = The fugitive unit contains compressor seals.</p> <p>Flanges = The fugitive unit contains flanges.</p> <p>Open-ended Valves = The fugitive unit contains open-ended valves.</p> <p>Pressure Relief Valves = The fugitive unit contains pressure relief valves.</p> <p>Process Drains = The fugitive unit has process drains.</p> <p>Pump Seals = The fugitive unit contains pump seals.</p> <p>Rupture Disks = The fugitive unit has pressure relief valves equipped with rupture disks.</p> <p>Title 30 TAC § 115.352 Applicable = Site is a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether manufacturing process or a natural gas/gasoline processing operation as defined in 30 TAC 115.10.</p> <p>Valves (other than pressure relief and open-ended) = The fugitive unit contains valves other than pressure relief valves or open-ended valves or lines.</p> <p>Alternate Control Requirement = The TCEQ Executive Director has not approved an alternate method for demonstrating and documenting continuous compliance with an alternate control requirement or exemption criteria for flanges or no alternate has been requested.</p> <p>Instrumentation Systems = The fugitive unit has instrumentation systems, as defined in 40 CFR § 63.161, that meet 40 CFR § 63.169.</p> <p>Less Than 250 Components at Site = Fugitive unit not located at site with less than 250 fugitive components.</p> <p>Sampling Connection Systems = The fugitive unit has sampling connection systems, as defined in 40 CFR § 63.161, that meet 40 CFR § 63.169.</p> <p>Weight Percent VOC = All components contact a process fluid that contains greater than or equal to 10% VOC by weight.</p> <p>50% by Volume = Compressors are not in hydrogen service or are in hydrogen service and the hydrogen content cannot be reasonably expected to always exceed 50% by volume.</p> <p>Complying with § 115.352(1) = No valves are complying with § 115.352(1).</p> <p>Complying With § 115.352(1) = No open-ended valves and lines are complying with § 115.352(1).</p> <p>Complying with 30 TAC § 115.352(1) = Process drains are not complying with the requirements in 30 TAC § 115.352(1).</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Complying with 30 TAC § 115.352(1) = Flanges are complying with the requirements in 30 TAC § 115.352(1).</p> <p>Reciprocating Compressors Or Positive Displacement Pumps = The fugitive unit does not have reciprocating compressors or positive displacement pumps used in natural gas/gasoline processing operations.</p> <p>Shaft Seal System = Pump seals are not equipped with a shaft seal system that prevents or detects emission of VOC from the seal.</p> <p>TVP 0.002 PSIA or Less = The fugitive unit has components or systems that contact a process fluid containing VOC having a true vapor pressure less than or equal to 0.002 psia at 68 degrees Fahrenheit.</p> <p>Shaft Seal System = Compressors are not equipped with a shaft sealing system that prevents or detects emission of VOC from the seal.</p> <p>TVP of Process Fluid VOC <= 0.044 psia at 68° F = No valves contact a process fluid with a TVP less than or equal to 0.044 psia at 68° F.</p> <p>TVP of Process Fluid VOC <= 0.044 PSIA AT 68° F = Process drains do not contact a process fluid containing VOC having a true vapor pressures less than or equal to 0.044 psia at 68 degrees Fahrenheit.</p> <p>TVP of Process Fluid VOC <= 0.044 PSIA AT 68° F = Flanges do not contact a process fluid containing VOC having a true vapor pressures less than or equal to 0.044 psia at 68 degrees Fahrenheit.</p> <p>Complying with 30 TAC § 115.352(1) = No pump seals are complying with the requirements in 30 TAC § 115.352(1).</p> <p>TVP of Process Fluid VOC <= 0.044 PSIA AT 68° F = Compressor seals do not contact a process fluid containing VOC having a true vapor pressures less than or equal to 0.044 psia at 68 degrees Fahrenheit.</p> <p>TVP of Process Fluid VOC > 0.044 psia at 68° F = Valves contact a process fluid with a TVP greater than 0.044 psia at 68° F.</p> <p>TVP of Process Fluid VOC > 0.044 PSIA AT 68° F = Flanges contact a process fluid containing VOC having a TVP greater than 0.044 psia at 68 degrees Fahrenheit.</p> <p>Complying With § 115.352(1) = No compressor seals are complying with the requirements in 30 TAC § 115.352(1).</p>
EOEGFUG	30 TAC Chapter 115, Pet. Refinery & Petrochemicals	R5352-2	<p>Agitators = The fugitive unit does not contain agitators.</p> <p>Components Utilizing Alternative Work Practice in § 115.358 = No components in the fugitive unit are using the alternative work practice under § 115.358.</p> <p>Compressor Seals = The fugitive unit does not contain compressor seals.</p> <p>Flanges = The fugitive unit contains flanges.</p> <p>Open-ended Valves = The fugitive unit contains open-ended valves.</p> <p>Pressure Relief Valves = The fugitive unit does not contain pressure relief valves.</p> <p>Process Drains = The fugitive unit has process drains.</p> <p>Pump Seals = The fugitive unit contains pump seals.</p> <p>Rupture Disks = The fugitive unit has pressure relief valves equipped with rupture disks.</p> <p>Title 30 TAC § 115.352 Applicable = Site is a petroleum refinery, synthetic organic chemical, polymer resin or methyl tert-butyl ether manufacturing process or a natural gas/gasoline processing operation as defined in 30 TAC 115.10.</p> <p>Valves (other than pressure relief and open-ended) = The fugitive unit contains valves other than pressure relief valves or open-ended valves or lines.</p> <p>Alternate Control Requirement = The TCEQ Executive Director has not approved an alternate method for demonstrating and documenting continuous compliance with an alternate control requirement or exemption criteria for flanges or no alternate has been requested.</p> <p>Instrumentation Systems = The fugitive unit has instrumentation systems, as defined in 40 CFR § 63.161, that meet 40 CFR § 63.169.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Less Than 250 Components at Site = Fugitive unit not located at site with less than 250 fugitive components.</p> <p>Sampling Connection Systems = The fugitive unit has sampling connection systems, as defined in 40 CFR § 63.161, that meet 40 CFR § 63.169.</p> <p>Weight Percent VOC = All components contact a process fluid that contains greater than or equal to 10% VOC by weight.</p> <p>Complying with § 115.352(1) = No valves are complying with § 115.352(1).</p> <p>Complying With § 115.352(1) = No open-ended valves and lines are complying with § 115.352(1).</p> <p>Complying with 30 TAC § 115.352(1) = Process drains are not complying with the requirements in 30 TAC § 115.352(1).</p> <p>Complying with 30 TAC § 115.352(1) = Flanges are complying with the requirements in 30 TAC § 115.352(1).</p> <p>Reciprocating Compressors Or Positive Displacement Pumps = The fugitive unit does not have reciprocating compressors or positive displacement pumps used in natural gas/gasoline processing operations.</p> <p>Shaft Seal System = Pump seals are equipped with a shaft seal system that prevents or detects emission of VOC from the seal.</p> <p>TVP 0.002 PSIA or Less = The fugitive unit has components or systems that contact a process fluid containing VOC having a true vapor pressure less than or equal to 0.002 psia at 68 degrees Fahrenheit.</p> <p>TVP of Process Fluid VOC <= 0.044 psia at 68° F = Valves contact a process fluid with a TVP less than or equal to 0.044 psia at 68° F.</p> <p>TVP of Process Fluid VOC <= 0.044 PSIA AT 68° F = Process drains contact a process fluid containing VOC having a true vapor pressures less than or equal to 0.044 psia at 68 degrees Fahrenheit.</p> <p>TVP of Process Fluid VOC <= 0.044 PSIA AT 68° F = Flanges contact a process fluid containing VOC having a true vapor pressures less than or equal to 0.044 psia at 68 degrees Fahrenheit.</p> <p>Complying with 30 TAC § 115.352(1) = Pump seals are complying with the requirements in 30 TAC § 115.352(1).</p> <p>TVP of Process Fluid VOC > 0.044 psia at 68° F = No valves contact a process fluid with a TVP greater than 0.044 psia at 68° F.</p> <p>TVP of Process Fluid VOC > 0.044 PSIA AT 68° F = Flanges do not contact a process fluid containing VOC having a TVP greater than 0.044 psia at 68 degrees Fahrenheit.</p>
EOEGFUG	40 CFR Part 63, Subpart H	63H160-1	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNSAFE TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS UNSAFE TO INSPECT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>DIFFICULT TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS DIFFICULT TO INSPECT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT PRESENT</p> <p>EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE = NONE OF THE EQUIPMENT IN ORGANIC HAP SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR IS IN HEAVY LIQUID SERVICE</p> <p>QIP = UNIT OPTS TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p>
EOEGFUG	40 CFR Part 63, Subpart H	63H160-2	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>BYPASS LINES = FUGITIVE UNIT WITH A CLOSED-VENT SYSTEM DOES NOT CONTAIN A BY-PASS LINE THAT COULD DIVERT A VENT STREAM AWAY FROM THE CONTROL DEVICE AND TO THE ATMOSPHERE</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>UNSAFE TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS UNSAFE TO INSPECT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>DIFFICULT TO INSPECT = FUGITIVE UNIT CONTAINS ANY CLOSED-VENT SYSTEM WITH PARTS DESIGNATED AS DIFFICULT TO INSPECT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p>
32MT3	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to use a continuous flow monitor on each inlet of each cooling tower in accordance with § 115.764(a)(1), (b)(1), or (h)(1).</p> <p>Total Strippable VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and specified HRVOCs in ppbw is being used.</p>
32MT3	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-2	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to use a continuous flow monitor on each inlet of each cooling tower in accordance with § 115.764(a)(1), (b)(1), or (h)(1).</p> <p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = Speciated strippable HRVOC concentration is being determined by sampling.</p>
32MT4	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-1	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to use a continuous flow monitor on each inlet of each cooling tower in accordance with § 115.764(a)(1), (b)(1), or (h)(1).</p> <p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = A continuous on-line monitor capable of providing total HRVOC and speciated HRVOCs in ppbw is being used.</p>
32MT4	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-2	<p>Cooling Tower Heat Exchange System Exemptions = The cooling tower heat exchange system does not qualify for an exemption.</p> <p>Jacketed Reactor = The cooling tower heat exchange system is not in dedicated service to a jacketed reactor.</p> <p>Alternative Monitoring = Complying with the specified monitoring in 30 TAC § 115.764.</p> <p>Design Capacity = Design capacity to circulate 8000 gpm or greater.</p> <p>Finite Volume System = The cooling tower heat exchange system is complying with the requirements in § 115.764(a).</p> <p>Modified Monitoring = NOT USING MINOR MODIFICATIONS TO THE MONITORING AND TESTING METHODS IN 30 TAC § 115.764.</p> <p>Flow Monitoring/Testing Method = Choosing to use a continuous flow monitor on each inlet of each cooling tower in accordance with § 115.764(a)(1), (b)(1), or (h)(1).</p> <p>Total Strippalbe VOC = The cooling tower heat exchange system is complying with the requirements of § 115.764(a).</p> <p>On-Line Monitor = Speciated strippable HRVOC concentration is being determined by sampling.</p>
32MT9	30 TAC Chapter 115, HRVOC Cooling Towers	R5760-1	<p>Cooling Tower Heat Exchange System Exemptions = Each individual heat exchanger of the cooling tower heat exchange system does not have greater than 100 ppmw HRVOCs in the process side fluid.</p>
32ANALYZER	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>
32MAINAN	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Exempt Date = The vent gas stream is not exempt.</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Continuous emissions monitoring system in lieu of testing requirements in § 115.725(a).</p>
32MAINAN	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>
32MAINT	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Exempt Date = The vent gas stream is not exempt.</p> <p>Vent Gas Stream Control = Vent gas stream is controlled by a flare.</p>
32MAINT	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
32MAINT	40 CFR Part 63, Subpart G	63G113-1	<p>Control Device = No recovery device.</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
32OXYAN	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Exempt Date = The vent gas stream is not exempt.</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Continuous emissions monitoring system in lieu of testing requirements in § 115.725(a).</p>
32OXYAN	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>
32T111OH	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is less than 0.011 scm/min or the VOC concentration is less than 500 ppmv.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
32T111OH	40 CFR Part 63, Subpart G	63G113-1	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = No recovery device.</p> <p>Overlap = Title 40 CFR Part 60, Subpart NNN</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>Regulation = The process vent is subject to the provisions of 40 CFR Part 60, Subpart NNN and 40 CFR Part 63, Subpart G, and the owner or operator is electing to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is less than to 50 ppm.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>NSPS TRE Index Value = TRE index value is greater than 8 as calculated using the appropriate equation from 40 CFR Part 60, Subparts III, NNN or RRR.</p>
32T168OH	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is less than 0.011 scm/min or the VOC concentration is less than 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
32T168OH	40 CFR Part 63, Subpart G	63G113-1	<p>Control Device = No recovery device.</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system does not contain by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
32UGCAN	30 TAC Chapter 115, HRVOC Vent Gas	R5720-1	<p>Alternative Monitoring = Not using alternative monitoring and testing methods.</p> <p>HRVOC Concentration = The vent gas stream has a HRVOC concentration of at least 100 ppmv at some times.</p> <p>Max Flow Rate = The vent gas stream has a maximum potential flow rate greater than 100 dry standard cubic feet per hour (ft³/hr).</p> <p>Exempt Date = The vent gas stream is not exempt.</p> <p>Minor Modification = Not using any minor modification to the monitoring and testing methods of the rule.</p> <p>Vent Gas Stream Control = Vent gas stream is uncontrolled.</p> <p>Process Knowledge = Process knowledge and engineering calculations are used to determine HRVOC emissions during emission events and scheduled startup, shutdown, and maintenance activities.</p> <p>Waived Testing = The executive director has not waived testing for identical vents.</p> <p>Testing Requirements = Continuous emissions monitoring system in lieu of testing requirements in § 115.725(a).</p>
32UGCAN	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.</p>
32V144OH	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p> <p>Combined 24-Hour VOC Weight = Combined VOC weight is less than or equal to 100 pounds (45.4 kg).</p> <p>VOC Concentration = VOC concentration is greater than or equal to 612 ppmv.</p> <p>VOC Concentration/Emission Rate @ Max Operating Conditions = The VOC concentration or emission rate is less than the</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			applicable exemption limit at maximum actual operating conditions and the alternate recordkeeping requirements of 30 TAC § 115.126(4) are being selected.
32V150OH	30 TAC Chapter 115, Vent Gas Controls	R5121-108	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p>
32V150OH	30 TAC Chapter 115, Vent Gas Controls	R5121-109	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p>
32V150OH	30 TAC Chapter 115, Vent Gas Controls	R5121-UF	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p>
32V150OH	40 CFR Part 63, Subpart G	63G113-108	<p>Control Device = Thermal hazardous waste incinerator meeting the requirement of 40 CFR § 63.116(b)(5).</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
32V150OH	40 CFR Part 63, Subpart G	63G113-109	Control Device = Thermal hazardous waste incinerator meeting the requirement of 40 CFR § 63.116(b)(5).

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
32V150OH	40 CFR Part 63, Subpart G	63G113-UF	<p>Control Device = No recovery device.</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
32V156OH	30 TAC Chapter 115, Vent Gas Controls	R5121-UF	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>
32V176OH	30 TAC Chapter 115, Vent Gas Controls	R5121-108	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p>
32V176OH	30 TAC Chapter	R5121-109	Alternate Control Requirement = Alternate control is not used.

Unit ID	Regulation	Index Number	Basis of Determination*
	115, Vent Gas Controls		<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C).</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p>
32V176OH	30 TAC Chapter 115, Vent Gas Controls	R5121-COF	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p>
32V176OH	40 CFR Part 63, Subpart G	63G113-COF	<p>Alternate Monitoring Parameters = The EPA Administrator has not approved alternate monitoring parameters or alternate monitoring parameters are not used.</p> <p>Control Device = Flare</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent meets the definition of a Group 1 process vent.</p> <p>Continuous Monitoring = Complying with the continuous monitoring requirements of 40 CFR §§ 63.114, 63.117, and 63.118.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Indicator = A flow indicator is installed and operated at the entrance of the by-pass line.</p> <p>Performance Test = No previous performance test was conducted.</p>
32V181OH	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Control Device Type = Smokeless flare</p> <p>Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.</p>
32V182OH	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Alternate Control Requirement = Alternate control is not used.</p> <p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			Control Device Type = Smokeless flare Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
32V219OH	30 TAC Chapter 115, Vent Gas Controls	R5121-108	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C). Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
32V219OH	30 TAC Chapter 115, Vent Gas Controls	R5121-109	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Direct flame incinerator in which the vent gas stream is burned at a temperature or at least 1300° F (704 C). Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
32V219OH	30 TAC Chapter 115, Vent Gas Controls	R5121-UF	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a noncombustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
32V761OH	30 TAC Chapter 115, Vent Gas Controls	R5121-UF	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2. Control Device Type = Smokeless flare Vent Type = Title 30 TAC Chapter 115, Subchapter B, Vent Gas Control rules are applicable and the vent is not specifically classified under the rule.
33HOTWELL	30 TAC Chapter 115, Vent Gas Controls	R5121-1	Alternate Control Requirement = Alternate control is not used. Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source. Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is less than 0.011 scm/min or the VOC concentration is less than 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
33T106OH	30 TAC Chapter 115, Vent Gas Controls	R5121-1	<p>Chapter 115 Division = The vent stream does not originate from a source for which another Division in 30 TAC Chapter 115 establishes a control requirement, emission specification, or exemption for that source.</p> <p>Total Design Capacity = Total design capacity is greater than or equal to 1,100 tons per year for all chemicals produced within that unit.</p> <p>Combustion Exhaust = The vent stream is not from a combustion unit exhaust or the combustion unit is used as a control device for a vent stream originating from a non-combustion source subject to 30 TAC Chapter 115, Subchapter B, Division 2.</p> <p>Flow Rate or VOC Concentration = Flow rate is less than 0.011 scm/min or the VOC concentration is less than 500 ppmv.</p> <p>40 CFR 60 Subpart NNN Requirements = The distillation unit vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart NNN: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p> <p>Vent Type = Vent gas stream originates from a synthetic organic chemical manufacturing industry reactor process or distillation operation, as defined in 30 TAC § 115.10.</p> <p>40 CFR 60 Subpart RRR Requirements = The reactor process vent gas stream satisfies neither of the following requirements of 40 CFR Part 60, Subpart RRR: TRE index value is greater than 8.0; or TRE index value is greater than 1.0 without the use of VOC emission control devices.</p>
33T106OH	40 CFR Part 63, Subpart G	63G113-1	<p>Control Device = No recovery device.</p> <p>Overlap = Title 40 CFR Part 63, Subpart G only</p> <p>Group 1 = The process vent is a Group 2 process vent.</p> <p>Halogenated = Vent stream is not halogenated.</p> <p>Regulation = Owners or operator is required to comply only with the requirements of 40 CFR Part 63, Subpart G.</p> <p>HAP Concentration = HAP concentration is not needed to determine applicability.</p> <p>By-pass Lines = The vent system contains by-pass lines that can divert the vent stream from the control device.</p> <p>Flow Rate = Flow rate is not needed to determine applicability.</p> <p>Electing Control = Not electing to control the process vent to the levels required in 40 CFR § 63.113(a)(1) or (a)(2).</p> <p>Flow Indicator = By-pass line valve is secured with a car-seal or lock-and-key type configuration.</p> <p>MACT TRE Index Value = TRE index value is greater than 4.0 as calculated using the procedures of 40 CFR § 63.115(d).</p>
32T111OH	40 CFR Part 60, Subpart NNN	60NNN-1	<p>Subpart NNN Chemicals = The distillation unit produces any chemical listed in 40 CFR § 60.667 as a product, co-product, by-product, or intermediate.</p> <p>Total Resource Effectiveness = TRE index value greater than 8.0 not from a halogenated vent stream.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Construction/Modification Date = After December 30, 1983.</p> <p>Subpart NNN Control Device = Condenser.</p> <p>Vent Type = Distillation unit not discharging vent stream into a vapor recovery system.</p> <p>Distillation Unit Type = Does not qualify for any exemption under § 60.660(c)(1)-(3).</p> <p>Total Design Capacity = 1 gigagram per year or greater.</p> <p>Vent Stream Flow Rate = Flow rate greater than or equal to 0.008 scm/min.</p> <p>Organic Monitoring Device = A recovery device specific monitoring device is used to demonstrate compliance with the TRE index value limit of § 60.662(c).</p>
PRO32EOEG	40 CFR Part 63, Subpart F	63F102-1	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>Heat Exchange System = No heat exchange system is utilized.</p>
PRO32EOHE	40 CFR Part 63, Subpart F	63F104-1	<p>Applicable Chemicals = The chemical manufacturing process unit manufactures, as a primary product, one or more of the chemicals listed in 40 CFR § 63.100(b)(1)(i) or 40 CFR § 63.100(b)(1)(ii).</p> <p>Intervening Cooling Fluid = There is no intervening cooling fluid containing less than 5 percent by weight of total HAPs listed in Table 4 of 40 CFR Part 63, Subpart F, between the process and cooling water.</p> <p>Table 2 HAP = The chemical manufacturing process unit uses as a reactant or manufactures, as a product or co-product, one or more of the organic hazardous air pollutants in Table 2.</p> <p>Table 4 HAP Content = The recirculating heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 4 of title 40 CFR Part 63, Subpart F.</p> <p>Alternate Means of Emission Limitation = No alternative means of emission limitation has been approved by the EPA Administrator to achieve a reduction in organic HAP emission or no alternate has been requested.</p> <p>NPDES Permit = The once-through heat exchange system is not subject to NPDES permit with an allowable discharge limit of 1 part per million or less above influent concentration or 10 percent or less above influent concentration.</p> <p>Meets 40 CFR 63.104(a)(4)(i)-(iv) = The once-through heat exchange system is not subject to an NPDES permit that meets 40 CFR § 63.104(a)(4)(i) - (iv).</p> <p>Heat Exchange System = A heat exchange system is utilized.</p> <p>Table 9 HAP Content = The once-through heat exchange system is not used exclusively to cool process fluids that contain less than 5 percent by weight of total HAPs listed in Table 9 of 40 CFR Part 63, Subpart G.</p> <p>Cooling Water Monitored = The cooling water is being monitored for the presence of one or more HAPs or other representative substances whose presence in cooling water indicates a leak.</p> <p>Cooling Water Pressure = The heat exchange system is not operated with the minimum pressure on the cooling water side at least 35 kilopascals greater than the maximum pressure on the process side.</p>

* - The "unit attributes" or operating conditions that determine what requirements apply

NSR Versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

The status of air permits and applications and a link to the Air Permits Remote Document Server is located at the following Web site:

www.tceq.texas.gov/permitting/air/nav/air_status_permits.html

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 55046	Issuance Date: 07/13/2010
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.264	Version No./Date: 09/04/2000
Number: 106.265	Version No./Date: 09/04/2000
Number: 106.355	Version No./Date: 11/01/2001
Number: 106.371	Version No./Date: 09/04/2000
Number: 106.373	Version No./Date: 09/04/2000
Number: 106.412	Version No./Date: 09/04/2000
Number: 106.433	Version No./Date: 09/04/2000
Number: 106.452	Version No./Date: 09/04/2000
Number: 106.454	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.476	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.492	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 106.512	Version No./Date: 06/13/2001
Number: 106.532	Version No./Date: 09/04/2000

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sand-blasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected

Compliance Assurance Monitoring (CAM):

Compliance Assurance Monitoring (CAM) is a federal monitoring program established under Title 40 Code of Federal Regulations Part 64 (40 CFR Part 64).

Emission units are subject to CAM requirements if they meet the following criteria:

1. the emission unit is subject to an emission limitation or standard for an air pollutant (or surrogate thereof) in an applicable requirement;
2. the emission unit uses a control device to achieve compliance with the emission limitation or standard specified in the applicable requirement; and
3. the emission unit has the pre-control device potential to emit greater than or equal to the amount in tons per year for a site to be classified as a major source.

The following table(s) identify the emission unit(s) that are subject to CAM:

Unit/Group/Process Information	
ID No.: 32V156OH	
Control Device ID No.: 26UTLFLR	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-UF
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No Pilot Flame	
<p>Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.</p>	

Unit/Group/Process Information	
ID No.: 32V181OH	
Control Device ID No.: 26UTLFLR	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No Pilot Flame	
<p>Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.</p>	

Unit/Group/Process Information	
ID No.: 32V182OH	
Control Device ID No.: 26UTLFLR	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-1
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No Pilot Flame	
<p>Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.</p>	

Unit/Group/Process Information	
ID No.: 32V219OH	
Control Device ID No.: 60MN108INC	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-108
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Minimum Combustion Temperature = 1585 degrees Fahrenheit	
<p>Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.</p>	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: 32V219OH	
Control Device ID No.: 60MN109INC	Control Device Type: Thermal Incinerator (Direct Flame Incinerator/Regenerative Thermal Oxidizer)
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-109
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: once per day	
Averaging Period: n/a*	
Deviation Limit: Minimum Combustion Temperature = 1585 degrees Fahrenheit	
Basis of CAM: It is widely practiced and accepted to use performance tests, manufacturer's recommendations, engineering calculations and/or historical data to establish a minimum temperature for thermal incinerators. This minimum temperature must be maintained in order for the proper destruction efficiency. Operation below the minimum combustion temperature will result in incomplete combustion and potential noncompliance with emission limitations and/or standards. The monitoring of the combustion temperature of a thermal incinerator is commonly required in federal and state rules, including: 40 CFR Part 60, Subparts III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; 40 CFR Part 63, Subparts G, R, DD, EE, and HH; and 30 TAC Chapter 115.	

*The permit holder may elect to collect monitoring data on a more frequent basis and calculate the average as specified by the minimum frequency, for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis and shall not be collected and used in particular instances to avoid reporting deviations.

Unit/Group/Process Information	
ID No.: 32V219OH	
Control Device ID No.: 26UTLFLR	Control Device Type: Flare
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Vent Gas Controls	SOP Index No.: R5121-UF
Pollutant: VOC	Main Standard: § 115.122(a)(1)
Monitoring Information	
Indicator: Pilot Flame	
Minimum Frequency: Continuous	
Averaging Period: n/a	
Deviation Limit: No Pilot Flame	
<p>Basis of CAM: It is widely practiced and accepted to monitor the flare pilot flame by closed circuit cameras, thermocouples and visual inspection. The presence of the pilot flame demonstrates that VOC emissions are combusted. Monitoring the presence of a pilot flame is required in many federal rules, including: 40 CFR Part 60, Subparts K, III, NNN, QQQ, and RRR; 40 CFR Part 61, Subparts BB and FF; and 40 CFR Part 63, Subparts G, R, W, DD, and HH.</p>	

Compliance Review

1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on April 3, 2017.

Site rating: 0.21 / Satisfactory

Company rating: 0.74 / Satisfactory

(*High < 0.10; Satisfactory ≥ 0.10 and ≤ 55 ; Unsatisfactory > 55*)

2. Has the permit changed on the basis of the compliance history or site/company rating?No

Site/Permit Area Compliance Status Review

1. Were there any out-of-compliance units listed on Form OP-ACPS?No

2. Is a compliance plan and schedule included in the permit?No

Available Unit Attribute Forms

OP-UA1 - Miscellaneous and Generic Unit Attributes

OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes

OP-UA3 - Storage Tank/Vessel Attributes

OP-UA4 - Loading/Unloading Operations Attributes

OP-UA5 - Process Heater/Furnace Attributes

OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes

OP-UA7 - Flare Attributes

OP-UA8 - Coal Preparation Plant Attributes

OP-UA9 - Nonmetallic Mineral Process Plant Attributes

OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes

OP-UA11 - Stationary Turbine Attributes

OP-UA12 - Fugitive Emission Unit Attributes

OP-UA13 - Industrial Process Cooling Tower Attributes

OP-UA14 - Water Separator Attributes

OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes

OP-UA16 - Solvent Degreasing Machine Attributes

OP-UA17 - Distillation Unit Attributes

OP-UA18 - Surface Coating Operations Attributes

OP-UA19 - Wastewater Unit Attributes

OP-UA20 - Asphalt Operations Attributes

OP-UA21 - Grain Elevator Attributes

OP-UA22 - Printing Attributes

OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes

OP-UA25 - Synthetic Fiber Production Attributes

OP-UA26 - Electroplating and Anodizing Unit Attributes

OP-UA27 - Nitric Acid Manufacturing Attributes

OP-UA28 - Polymer Manufacturing Attributes

OP-UA29 - Glass Manufacturing Unit Attributes

OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semi-chemical Pulp Mill Attributes

OP-UA31 - Lead Smelting Attributes

OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes

OP-UA33 - Metallic Mineral Processing Plant Attributes

OP-UA34 - Pharmaceutical Manufacturing

OP-UA35 - Incinerator Attributes

OP-UA36 - Steel Plant Unit Attributes

OP-UA37 - Basic Oxygen Process Furnace Unit Attributes

OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes

OP-UA39 - Sterilization Source Attributes

OP-UA40 - Ferroalloy Production Facility Attributes

OP-UA41 - Dry Cleaning Facility Attributes

OP-UA42 - Phosphate Fertilizer Manufacturing Attributes

OP-UA43 - Sulfuric Acid Production Attributes

OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
OP-UA45 - Surface Impoundment Attributes
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/De-painting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes